

## Claims

1. A safety device for indicating relative rotational displacement of any one of a plurality of rotatably securable fasteners, the device comprising a holder in  
5 which a plurality of position indicators for indicating rotational position of the respective fasteners are captively but rotatably mounted and at least one fastener cover which is removably locatable over a fastener and attachable to a corresponding position indicator so as link movement of the fastener and the said position indicator.  
10
2. A safety device according to claim 1 wherein one or each position indicator includes an indicator portion which, when in a first position, which in use corresponds to an initial fastener position, is hidden from view by the holder, but when in a second position, which in use corresponds to a loosened  
15 fastener position is visible outside the holder.
3. A safety device according to claim 1 wherein one or each position indicator includes an indicator portion made highly visible so as to give an at-a-glance indication of a loose nut.  
20
4. A safety device according to any preceding claim wherein the position indicators are a snap fit in apertures in the holder.
5. A safety device according to any previous claim wherein the holder is an  
25 annular disc.
6. A safety device according to any previous claim wherein the or each position indicator is asymmetrical and is thereby capable of moving position in use when not linked to a fastener cover by means of centripetal force about a  
30 fastener when in circular motion on a wheel.

7. A safety device according to any previous claim wherein one or each position indicator is attachable to a corresponding fastener cover by means of splines on one or both of the indicator and the cover.
- 5 8. A safety device according to any previous claim wherein one or each fastener cover is attachable in use to a fastener by means of splines on the fastener cover.
9. A kit of parts for a safety device according to any previous claim comprising  
10 a holder, a plurality of position indicators and a plurality of fastener covers.
10. A wheel equipped with a safety device according to any of claims 1 to 9.
11. A safety device as hereinbefore described with reference to and as illustrated  
15 by any of figures 1 to 6.